



**BOLDLY EXCEEDING EXPECTATIONS.**

## **DYNA GOLD, API SF / CD, SAE 20W50**

### **MULTIGRADE ENGINE OIL**

Dyna Gold API SF / CD, SAE 20W50 is a multigrade diesel & petrol engine oil formulated with an

optimised combination of base oils and a balanced additive system.

### **FEATURES & BENEFITS**

- Good protection against rust and corrosion for longer equipment life and reduced operating costs.
- Thermal and oxidation stability that controls sludge build-up and deposits

### **APPLICATION**

Gasoline and diesel powered equipment where API SF / CD level performance is required. On-highway light and medium duty trucking. Off-highway industries including: construction,

quarrying, and agriculture.

It is also available in other SAE grades in 200 litres packing: 15W40, 30, 40 & 50

### **SPECIFICATION OF DYNA GOLD, API CD / SF, SAE 20W50, 15W40, 30, 40 & 50**

PARAMETERS	SAE20W50	SAE15W40	SAE30	SAE40	SAE50
<b>Viscosity, ASTM D 445</b>					
cSt @ 40 Deg C	176.8	126.5	107.12	141.4	171.3
cSt @ 100 Deg C	17.93	14.42	11.15	14.6	17.42
Viscosity Index, ASTM D 2270	111	114	88	102	110
Total Base mg KOH/g, ASTM D 2896	5	5	5	5	5
Pour Point, Deg C, ASTM D 97	-9	-9	-9	-9	-9
Flash Point, Deg C, ASTM D 93	224	218	220	224	218
Density @ 30 Deg C Kg/L, ASTM D 4052	0.8844	0.8786	0.8870	0.8851	0.8844
Colour ASTM D 1500	L3	L2.5	L2.5	L2.5	L2.5

These characteristics are typical of current production.

Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.

**MANUFACTURED BY**  
D.K. LUBRICANTS (M) SDN BHD  
SELANGOR D.E., MALAYSIA

**INTERNATIONALLY MARKETING BY**  
KISMAT PETROLEUM TRADING PTE LTD,  
SINGAPORE



**DYNAMOLUBRICANTS.COM**