# DYNA MO LUBRICANTS

### **BOLDLY EXCEEDING EXPECTATIONS.**

## DYNA ZOOM, API SJ / JASO MA1, SAE 20W50

#### FOUR STROKE ENGINE OIL

Dyna Zoom Motorcycle Oil is a high-performance engine oil for 4 stroke 2 & 3 wheelers. This oil is a high viscosity index, 4 stroke engine oil.

Dyna Zoom Motorcycle Oil is a high performance conventional four-stroke motorcycle engine oil and is primarily intended for general use in all types of four-stroke motorcycles and engines. Dyna Zoom Motorcycle Oil 20W50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection.

#### **FEATURES & BENEFITS**

- Good wear protection helps extend engine life.
- Thermal and oxidation stability helps keep engines clean for smoother operation.
- Good corrosion protection for critical engine components.
- Broad viscosity range for year-round engine protection and performance.

#### APPLICATION

Dyna Zoom Motorcycle Oil is designed for engine oils where JASO MA or MA1 (T903: 2006) are required, as well as API SJ.

The oil is primarily for on-road, high-performance, 4-stroke bikes, however, it may be used in other types of on and off-road 4-cycle motorcycles.

Dyna Zoom Motorcycle Oil is designed for high

performance 4-stroke bikes to deliver optimum power and protection in all riding conditions.

It is suitable for all makes of 4-strokes bikes, both carburettor and fuel injected where API SJ (and earlier) and JASO MA or MAI specifications are recommended.

## SPECIFICATION OF DYNA ZOOM, API SJ / JASO MA1, SAE 20W50

PARAMETERS	TYPICAL PROPERTIES
Viscosity, ASTM D 445	
cSt @ 40 Deg C	176.92
cSt @ 100 Deg C	18.08
Viscosity Index, ASTM D 2270	113
Pour Point, Deg C, ASTM D 97	-15
Flash Point, Deg C, ASTM D 93	224
Density @ 30 Deg C Kg/L, ASTM D 4052	0.8826

These characteristics are typical of current production. Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.



