



**BOLDLY EXCEEDING EXPECTATIONS.**

## **DYNA ULTRA, API SN, ILSAC GF-4 SAE 5W30 & 10W30 PREMIUM GASOLINE ENGINE OIL**

Dyna Ultra API SN ILSAC GF-4, SAE 5W30 & 10W30 are premium synthetic gasoline engine oils designed to provide a high level of performance and protection under most operating conditions. The oil is formulated from high quality base oils combined with modern performance additives to help provide long engine life and protect critical engine parts from lubricant related failures for up to 8,000 kms or your vehicle's OEM recommended oil change interval, whichever is longer.

Dyna Ultra oils contain extra cleaning additive to help protect against sludge and engine deposits. Additionally, pour point depressants and a viscosity index (VI) improver are included in the product, where required, to provide the optimum viscosity and fluidity across a broad range of temperatures.

Dyna Ultra is available in two multi-viscosity grades: SAE 5W30 and 10W30.

### **FEATURES & BENEFITS**

- Helps extend engine life.
- Proven protection of critical engine parts from lubrication related failure for 8,000 kms or your vehicle's OEM recommended oil change interval, whichever is longer.
- Outstanding wear protection under a wide variety of operating conditions.
- Extra cleaning additive to help prevent the formation of sludge and harmful deposits.
- Easy cold starting.

### **APPLICATION**

It is engineered as per the requirement and use in gasoline engines & light duty trucks requiring API SN, SM, SL or SJ. They meet the latest ILSAC GF-4 specification. They also meet MIL\_L\_46152D & CID

A-A-52039B, GM 9986125/9986126 FORD M2C153-F/G/H, CHRYSLER MS 6395-H, as well as many Japanese and European vehicles.

## **SPECIFICATION OF DYNA ULTRA, API SN, ILSAC GF-4 SAE 5W30 & 10W30**

PARAMETERS	TYPICAL PROPERTIES SAE 5W30	TYPICAL PROPERTIES SAE 10W30
<b>Viscosity, ASTM D 445</b>		
cSt @ 40 Deg C	57.01	63.65
cSt @ 100 Deg C	9.95	10.65
<b>Viscosity Index, ASTM D 2270</b>	162.2	158
CCS, cP	6,080@-30°C	6,740@-25°C
<b>Pour Point, Deg C, ASTM D 97</b>	-29	-29
<b>Flash Point, Deg C, ASTM D 93</b>	218	219
<b>Density @ 30 Deg C Kg/L, ASTM D 4052</b>	0.8401	0.8451
<b>Colour ASTM D 1500</b>	L2	L2.5

These characteristics are typical of current production.

Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.

**MANUFACTURED BY**  
D.K. LUBRICANTS (M) SDN BHD  
SELANGOR D.E., MALAYSIA

**INTERNATIONALLY MARKETING BY**  
KISMAT PETROLEUM TRADING PTE LTD,  
SINGAPORE



**DYNAMOLUBRICANTS.COM**