



BOLDLY EXCEEDING EXPECTATIONS.

DYNA SUPER, API SN, SAE 5W30 & 10W40

PREMIUM GASOLINE ENGINE OIL

Dyna Super API SN, SAE 5W30 & 10W40 are premium, fully synthetic, API registered gasoline engine oils designed to provide a high level of performance and protection under most operating conditions. The oil is formulated from high quality base oils combined with modern performance additives to help provide long engine life and protect critical engine parts from lubricant related failures for up to 8,000 kms or your vehicle's OEM recommended oil change interval, whichever is longer.

APPROVALS

Certified by American Petroleum Institute as "DYNAMO SUPER, 10W-40, SN"

Certified by American Petroleum Institute as "DYNAMO SUPER, 5W-30, SN, Resource Conserving, ILSAC GF5

FEATURES & BENEFITS



- Helps extend engine life.
- Proven protection of critical engine parts from lubrication related failure for 8,000 kms or your vehicle's OEM recommended oil change interval, whichever is longer.

APPLICATION

It is engineered as per the requirement and use in gasoline engines & light duty trucks requiring API SN, SM, SL or SJ. They meet the latest ILSAC GF5 specification. They also meet MIL_L_46152D & CID

Dyna Super oils contain extra cleaning additive to help protect against sludge and engine deposits. Additionally, pour point depressants and a viscosity index (VI) improver are included in the product, where required, to provide the optimum viscosity and fluidity across a broad range of temperatures.

Dyna Super is available in two multi-viscosity grades: SAE 5W30 and 10W40.



- Outstanding wear protection under a wide variety of operating conditions.
- cleaning additive to help prevent the formation of sludge and harmful deposits.
- Easy cold starting.

A-A-52039B, GM 9986125/9986126 FORD M2C153-F/G/H, CHRYSLER MS 6395-H, as well as many Japanese and European vehicles.



BOLDLY EXCEEDING EXPECTATIONS.

SPECIFICATION OF DYNA SUPER, API SN, SAE 5W30 & 10W40

PARAMETERS	TYPICAL PROPERTIES SAE 5W30	TYPICAL PROPERTIES SAE 10W40
Viscosity, ASTM D 445		
cSt @ 40 Deg C	60.5	85.22
cSt @ 100 Deg C	10.39	13.84
Viscosity Index, ASTM D 2270	162	167
CCS, cP	6,080@-30°C	6,740@-25°C
Pour Point, Deg C, ASTM D 97	-30	-31
Flash Point, Deg C, ASTM D 93	204	202
Colour ASTM D 1500	L3	L3
Density @ 30 deg C	0.8433	0.8451

These characteristics are typical of current production.

Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.

MANUFACTURED BY
D.K. LUBRICANTS (M) SDN BHD
SELANGOR D.E., MALAYSIA

INTERNATIONALLY MARKETED BY
KISMAT PETROLEUM TRADING PTE LTD,
SINGAPORE



DYNAMOLUBRICANTS.COM